



36 Watt Panel 48"X12" LED Fixture
 Low Profile Ceiling Light



LED quantity:	360 Super-Bright 3014 SMD's
Light Color:	Warm / Natural / Day White
Color Temperature:	3000 – 6000 K
Lens Cover:	Optical PMMA
Operating Voltage A/C:	110 – 277
Frequency:	50HZ – 60HZ
Operating Temperature:	-30°F to + 160°F
CRI:	>80
Total Current/Power used:	36-38W
Optical Power:	38 Watts
Power Efficiency:	>0.95
Frame:	Aluminum
Luminous Flux:	3,000 -3,900
Electrical Standard:	RoHS, CE
Beam Angle of Each LED:	120°
Lifetime of Lamp:	50,000 hours +
IP:	50
Fixture Dimensions:	48" X 12" X 5.0" height
External Power Driver:	3.75" X 1.75" X 0.75"
Weight:	12 pounds

Installation:

For retrofit, bypass incoming fixture voltage (120 – 277 VOLTS A/C) directly to light power supply. This light replaces existing fixture. This should be done by qualified electrical professional. No modifications allowed to bulbs as this could cause damage to heat-sink, loosen electronics, and void warranty. Do not look directly at light at close range – very bright. All Bravolight products are certified CE & RoHS.

