



LED Light Specification
50 Watt MoonRaker Post

Applications: Indoor, Outdoor Post or vertical Mounted



| | |
|--------------------------|---|
| Light Color: | Day White (5800K) others avail. |
| LED Quantity: | 250 Epistar's |
| Operating Voltage A/C: | 120 - 277 |
| Working Voltage D/C: | 50 |
| Normal Operating Temp: | 115 front, <140 degrees heat-sink |
| Lamp Base | E40 (Mogul) and E27 (medium) |
| Light Efficiency: | >95 lm/w |
| Features: | Compact design allows many retrofit possibilities. Shatterproof design |
| Power Consumption: | 50 Watts |
| Power Factor: | >95% |
| Luminous Flux: | 4,500 - 5,000LM |
| CRI: | >75 |
| LED Panel Angle: | 360° |
| Lifetime of Lamp: | 50,000 hours + |
| Typical Mounting Height: | Up to 22 feet |
| Warranty: | 2 years from date of sale |
| Weight & Dimensions: | 2.5 lbs / 3.5" X 10.625" |

Installation:

For retrofit, bypass incoming fixture voltage (120 - 277 VOLTS A/C) directly to the lamp base. This should be done by qualified electrical professional. No modifications allowed to bulbs as this could cause damage to heat-sink, loosen electronics, and void warranty. Existing fixture socket may need to be adjusted. It is approximately the same width as a 400 watt metal halide bulb. Do not look directly at light at close range - very bright. All Bravolight products are certified CE & RoHS.

