



**10 WATT RECESSED LED FIXTURE**  
**LOW PROFILE CEILING LIGHT**  
**MOUNTS IN RECESSED CANS OR CEILING TILE GRIDS**



LED quantity:	168
Light Color:	Warm - Day White
Color Temperature:	3000 - 6000 K
Lens:	Tempered Glass
Operating Voltage A/C:	110 - 277
Frequency:	50HZ - 60HZ
Operating Temperature:	-30°F to + 160°F
CRI:	>80
Total Current/Power used:	0.085 Amps / 10 watts
Optical Power:	<b>9 Watts</b>
Power Efficiency:	>0.95
Surface Brightness:	7,200 -9,600 Lux
Luminous Flux:	720 - 960 Lm
Electrical Standard:	Class II, CE
Beam Angle of Each LED:	130°
Lifetime of Lamp:	50,000 hours +
IP:	50
Fixture Dimensions:	7.87" outside, 6" inner, 1.75" height
External Power Driver:	3.75" X 1.75" X 0.75"

**Installation Instructions:** Fixture should be mounted by a certified electrician or a professional electrical maintenance contractor or person with working knowledge of installing & maintaining this type of light. As with any electrical fixture, the power source should be off while installation is performed and follow all state and local electrical codes accordingly.

**Feb/2010**

**BVO10-10W-RECESS**